

BR111, BR222 and BR333



Sandvik's BR111, BR222 and BR333 models combine simplicity and cost-effectiveness with a class-leading power to weight ratio that is optimised for demolition and recycling applications. The three models match carriers in the 0.8 to 4.0 ton (1800-8800 lb) range, and all three breakers utilize a streamlined and lightweight design that sets a new standard in low weight and high power.

Features and values

- › Pressure Release System
- › Compact usability
- › Class-leading power to weight ratio
- › Single lower tool bushing
- › Integrated design
- › Service friendly

Models

Model	BR111	BR222	BR333
Working weight, kg (lb)	65.6 (144.3)	100.9 (222)	148.8 (327.4)
Impact rate, bpm	1000-2600	1100-2600	1050-2050
Operating pressure, bar (psi)	80-130 (1150- 1900)	100-150 (1450- 2200)	100-150 (1450- 2200)
Pressure relief min, bar (psi)	130-180 (1900- 2600)	150-200 (2200- 2900)	150-200 (2200- 2900)
Acceptable oil flow, l/min (gal/min)	15-33 (4-9)	20-48 (5-13)	30-63 (8-17)
Carrier weight limit, ton (lb)	0.8-1.8 (1800- 4000)	1.2-2.4 (2600- 5300)	2.0-4.0 (4400- 8800)
Noise level (2000/14/EC), dB(A)	121	127	123

This technical data is indicative only and subject to change without notice.