

GSL65D RENTAL		Rental Kit includes	
GENERATOR	GSL65D		
STANDBY POWER LTP KW/KVA	49.6/61.9		4 445 60
PRIME POWER PRP KW/KVA	47.8/59.7	Socket	- 1 x 415v 63amp;
VOLTAGE VOLT/FREQUENCY	400/50	Panel	- 1 x 415v 32amp
PHASES	3		- hard wire facility
ENGINE			
MANUFACTURER	Deutz		Fuel Valves (to allow connection
MODEL	BF4M2011C		
COOLING SYSTEM	Oil	to external fuel supply)	
FUEL	Diesel		
NUMBER AND DISPOSITION OF CYLINDERS	4 in Line	Fully Bunded Base	
DISPLACEMENT CC	3110	,	
ASPIRATION	Turbo	Automotio	Control Danal with two wire start
STARTING SYSTEM/ELECTRIC CIRCUIT (VOLT)	Electric/12	Automatic Control Panel with two wire start	
SPEED rpm	1500	option	
SPEED GOVERNOR STAND BY POWER LTP kW	Mechanical 56		
PRIME POWER PRP Kw	56	Battery Isolator Switch	
FUEL CONSUMPTION at 75% /100% prp L/h	10.7/14.6	,,	
ALTERNATOR	10.7714.0	Cingle Kerry	Sustam
ТҮРЕ	Stamford	Single Key	System
POLES	4		
VOLTAGE REGULATION SYSTEM	Electronic		
OVERALL DIMENSIONS AND WEIGHT			
LENGTH mm	2285		
WIDTH mm	920		
HEIGHT mm	1310		
WEIGHT Kg	1093		
FUEL TANK CAPACITY L	209		
RUNNING TIME @ 75% / 100% PRP h	19.5/14.3		
NOISE PRESSURE LEVEL at 7mt dB(A)	67		
GUARANTEED SOUND POWER LEVEL LWA dB(A)	93		

All quotes from PRAMAC UK LTD are valid for 30 days following the date of email transmission. Our company accepts no liability for the content of this email, or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing. The recipient should check this email and any attachments for the presence of viruses. The company accepts no liability for any damage caused by any virus transmitted by this email.