



After decades of success through its s-series/Small range of breakers Sandvik has released three new state of the art breakers BR555, BR777 and BR999. Incorporating the CBE plus operating principle without tierods all three of the new Sandvik Small range breakers are powerful, reliable and easy to maintain. Sandvik's small range breakers are your reliable long life solution to any breaking application for carriers between 3.4 and 12.5 ton..

Features and values

- › CBE plus operating principle.
- › Pivotal hose connecting block.
- › Sound suppressed.
- › Single body concept .
- › Single lower tool bushing.
- › Lower operating costs.

Models

Model	BR555	BR777	BR999
Working weight, kg (lb)	275 (610)	370 (820)	505 (1110)
Impact rate, bpm	600-1800	500-1700	450-800
Acceptable oil flow, l/min (gal/min)	35-90 (9-24)	40-120 (11-32)	50-150 (13-40)
Operating pressure, bar (psi)	90-140 (1300-2050)	90-140 (1300-2050)	100-140 (1450-2050)
Minicavator, tractor backhoe weight, t (lb)	3.4-8.0 (7500-17600)	4.6-9.0 (10100-19800)	7.0-12.5 (15400-27600)
Skid steer, robot weight (lb)	1.9-3.6 (4200-7900)	2.6-5.0 (5700-11000)	4.0-7.0 (8800-15400)

This technical data is indicative only and subject to change without notice.