








Specification Data Sheet | Model: H10ART-EU(W)



HIGHWAY TOW ABBI-ART 985 Ltr

The new Highway Tow ABBI Mk2 consists of a steel in steel U.N. (United Nations) approved IBC (Intermediate Bulk Container) suitable for transporting diesel fuel on the highway. The ABBI is fully bunded to ensure environmental compliance with Pollution Prevention Guidelines (PPG2).

-  Secure lockable access hatch to enclose pumping equipment.
-  110% bund capacity.
-  Direct access into the inner tank via manhole for cleaning and inspection.
-  Full load lifting is possible using the four lifting eyes.
-  Internal baffle for safe towing.
-  Trailer Type Approval Number: e11/2007*46*0769*00
-  Easily demountable from trailer.

SPECIFICATION

Standard Tank Fittings: 2" Fill Cap : Contents Gauge : 1" Pump Feed : Vacuum Vent with Back Pressure Relief: Generator Feed & Return Ports : Pump Bracket : Inspection Manhole : Bund Emptying Pipe.

Capacity (Brim Full) Litres:	985	Brake Specification:	200 x 50 auto reverse brakes
Capacity (Brim Full) Gallons:	210	Chassis:	Hot dipped galvanised
Dimensions Length (mm):	3390	Wheels & Tyres:	185R14 tyres on 5 stud wheel
Dimensions Width (mm):	1600	Mudguards:	Moulded polythene
Dimensions Height (mm):	1700	Jockey Wheel:	48mm telescopic jockey wheel. 1x rear dropleg
Cabinet Dimensions (mm) Opening Size (approx):	W730 x H350 x D350	Lighting:	EU 13 pin plug. Wired to ISO standard with fog & reverse lamps
Weight Unladen (kg):	660	Coupling Specification:	2000kg 50mm ball or 40mm eye as specified
Weight Laden (kg):	1500*	Design Approvals:	ADR IBC Type 31A, Type Approved Chassis
Suspension:	Single rubber suspension axle 1500kg gross	Design Standards:	Bunded to COP Regulations (PPG2)

Notes

* Specific gravity of diesel taken as 0.9 for this calculation

European Community Design Registration Number 001391049-0001/001391049-0002

Revision Date: 07/01/2016