

Technical sheet :

HYDRAULIC WINCH



Benefits

- Turns your telehandler into a crane.
- Extremely fast implementation on the MANITOU carriage.
- Easy steering from the cab or with the machine's remote control (optional).
- Fast and accurate movements.

Technical characteristics

- Hydraulic motor + end of cable automatic movement stop.
- Oil immersed negative break.
- Double or quadruple line pull (according to type).
- Homologated swivel self locking hook.
- Winch storage stand with sleeves for fork handling.
- Note: dimensions below are given for winch placed on its stands.
- MRT Vision+ : Significant hook speed increase through machine/attachment cooperation improvement.

Technical characteristics		Winch 5T (b)	Winch 7.2T
Load centre of gravity (mm)	c	350	192
Capacities			
Max. outreach (mm)	r1	541	238
Working height (mm)	h21	24000	36000
Capacity (kg)		5000	7200
Dimensions			
Overall length (mm)	l1	900	1200
Weight and dimensions			
Overall height (mm)	h17	1869	2408
Width (mm)		1080	1223
Depth (mm)	p5	838	638
Overall weight (kg)		450	700
Cable length (mm)		51000	76000
Cable loop		-	1
Working Parameters			
Machine Equipment		-	Hydraulic line
Working height/open attachment (mm)		24000	36000
Hook Speed (m/mn)		22	19
Hydraulic system		false	false

Machines compatibility	Winch 5T (b)	Winch 7.2T
Reference number	-	-
MT 1135	-	-
MT 1135 H easy ST5	-	-
MT 1335	-	-
MT 1440	-	-
MT 1440 A	-	-
MT 1440 HA	-	-
MT 1840	-	-
MT 1840 A	-	-
MT 1840 HA	-	-
MT-X 1440	-	-
MT-X 1440 A	-	-
MT-X 1840	-	-
MT-X 1840 A	-	-
Reference number E-RECO	999109	934500
MRT 1440 Easy T4 S2 400°	-	-
MRT 1640 Easy T4 S2 360°	-	-
MRT 1840 Easy T4 S2 360°	-	-
MRT 1840 Easy T4 S2 400°	-	-
MRT 2145 Easy T4 S2 360°	-	-
MRT 2145 Easy T4 S2 400°	-	-
MRT 2150 Privilege Plus	-	-
MRT 2470 Privilege Plus	-	X
MRT 2545 Easy T4 S2 360°	-	-
MRT 2545 Easy T4 S2 400°	-	-
MRT 2550 Privilege Plus	-	-
MRT 3050 Privilege Plus	X	-
MRT 3255 Privilege Plus	X	-
MRTX 1440 Easy 400°	-	-
MRTX 1640 Easy 360°	-	-
MRTX 1640 Easy 400°	-	-
MRTX 1840 Easy 360°	-	-
MRTX 1840 Easy 400°	-	-
MRTX 2145 Easy 360°	-	-
MRTX 2145 Easy 400°	-	-
MRTX 2150 Privilege Plus	-	-
MRTX 2470 Privilege Plus	-	X
MRTX 2545 Easy 360°	-	-
MRTX 2545 Easy 400°	-	-
MRTX 2550 Privilege Plus	-	-
MRTX 3050 Privilege Plus	X	-
MRTX 3255 Privilege Plus	X	-
Reference number E-RECO 2	-	53027311
MRT 3050 Privilege Plus	-	-
MRT 3255 Privilege Plus	-	X
MRTX 3050 Privilege Plus	-	-
MRTX 3255 Privilege Plus	-	X



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes